




## AQUA TURBO® FRMD/MIX-AS

Floatables removal device + floating downdraft mixer

Features the same as FRMD/MIX-SL but designed to allow operation at low water level by positioning the special adjustable scum weir beside the mixer rather than above it. The weir and submersible pump are mounted on an independent float connected to the mixer via a self-leveling linkage.





<u>Applications</u>: Removal of bulking + old sludge Removal + reuse of scum Sludge stabilization + biogas SBR

## Features:

Adjustable flow rate Purpose designed blockage free pump Reliable + non-clogging impeller Simple installation + removal



1.5 <u>– 55</u>kW 4 + 6 Pole speeds, direct drive Multiple pump flow rate options AISI 304/316 or other SS

## **Configurations:**

Pontoon mount only Vertical operation only 1 x Surface drive + Submerged pump Fixed or variable WL

Brusselsesteenweg 508 • B-1500 Halle - Belgium Tel.: +32/02 362 02 62 • Fax : +32/02 360 35 89 E-mail: asi@aquaturbo.com • http://www.aquaturbo.com

Çamlık Mah. Dinç Sok. No:4 D:83 PK.34774 Tel. 0216 540 99 64 • Fax. 0216 540 99 68 E-mail:info@etaekipman.com•http//:www.etaekipman.com